REF-IPF-8_instructions.pdf 1 8/10/22 9:07 AM

instapure®
SINCE 1975

# Installation Instructions for REF-IPF-8

1. Locate existing filter and remove it by turning the filter ¼ turn counterclockwise, then pull straight out.
2. Carefully remove the sanitary cap from the top of the new filter.
3. With the filter knob in a horizontal position, insert the new filter into the housing head and turn filter clockwise ¼ turn. The filter knob should now be aligned vertically. Be sure to apply pressure as you insert the filter and turn a full ¼ turn clockwise until you feel it stop.

   Note: Please ensure the filter is fully installed as it is required to activate the internal water valve. If the filter isn't properly installed, you may experience a slow flow or a chattering noise. If this occurs, please uninstall and reinstall the filter ensuring the filter is fully installed.
4. Run approximately 2.5 gallons of water from dispenser periodically to clear the system and to receive a good flow. If the water flow is slower than usual, please repeat Step 3.

   Note: Initial flow rate may be slower than expected. Full flow rate should be restored within 24-36 hours.
5. Inspect the filter for any noticeable leaks. If leaks are detected, please repeat Step 3.
6. To reset the filter monitor light, please refer to your refrigerator owner's manual for specific instructions.
7. Locate the included Water Filter Replacement Calendar and follow the instructions on the label.

Manufactured by: Aquamor, LLC Temecula, CA

| | |
|---|---|
| Flow Rate: | .5 gpm (1.89 lpm) |
| Operating Temperature: | 33°-100°F (0.6°-38°C) |
| Min Operating Pressure: | 20 psi (138 kPa) |
| Max Operating Pressure: | 100 psi (689 kPa) |
| Life: | 6 months or 300 gallons (1,136 liters) |

This REF-IPF-8 is Tested and Certified by NSF International against NSF/ANSI Standard 42 and 53 for the reduction of chlorine taste and odor, Endrin, 1, 2, 4-Trichlorobenzene, p-Dichlorobenzene. Refer to performance data sheet for complete list of claims.

This REF-IPF-8 is Certified by IAPMO R&T against NSF/ANSI Standard 42, 53, 372, 401, P473, and CSA B483.1 for the reduction of Chlorine taste and odor, Lead, VOC's, Mercury, Asbestos, Pharmaceuticals (such as Naproxen, Ibuprofen, and Phenytoin), BPA, PFOA/PFOS. Refer to performance data sheet for complete list of claims.

Installation shall comply with
applicable state and local regulations.

**For further questions or assistance, please call 1.970.212.4100**

Warning: To reduce the risk of property damage from water leakage, the filter bypass plug MUST be used when a filter replacement cartridge is not installed. For cold water applications only. Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Protect from freezing. REPLACE FILTER EVERY 6 MONTHS, OR IF BAD TASTE OR ODOR OCCUR. The risk associated with small parts can cause choking if swallowed. Keep children away from small parts during the replacement of the water filter.

Part Number: 803508

© 2022 Instapure Brands, Inc